

**Specific Test List: A.C.T. Voluntary Performance Guidelines**

Test	SAMPLE SIZE	Performance Time
<b>UPHOLSTERY:</b>		
1. Flammability: California TB 117 (2000), Section E	12" x 24"	3 - 5 days
2. Crocking (Wet & Dry): AATCC 8	8" x 24"	2 - 3 days
3. Lightfastness, 40 hours: AATCC 16, Option 1 or 3	8" x 8"	5 - 7 days
4. Brush Pill: ASTM D 3511	36" x 36"	3 - 4 days
5. Breaking (Tensile) Strength: ASTM D 5034	12" x 36"	3 - 4 days
6. Seam Slippage: ASTM D 4034	18" x 36"	3 - 4 days
7. Abrasion: (a or b)		
a) Wyzenbeek Method: ASTM D 4157 (#10 cotton duck)	18" x 36" - OR - Full Repeat	5 days minimum
b) Martindale Method: ASTM D 4966 (21 oz. Weight)	18" x 36" - OR - Full Repeat	5 days minimum
<b>DRAPERY &amp; CURTAINS:</b>		
1. Flammability: NFPA 701 - 1989 Small Scale	36" x 36"	3 - 5 days
2. Crocking (Wet & Dry): AATCC 8	8" x 24"	2 - 3 days
3. Lightfastness, 60 hours: AATCC 16 Option 1 or 3	8" x 8"	7 - 10 days
4. Seam Slippage: ASTM D 3597/D 434 For fabrics 6 oz/yd <sup>2</sup> and over	18" x 36"	3 - 4 days
<b>WALL COVERINGS:</b>		
<b>Direct Glue Wallcoverings:</b>		
1. Flammability: ASTM E 84 (Adhered)	4 yards	4 weeks
2. Crocking (Wet & Dry): AATCC 8	8" x 24"	2 - 3 days
3. Lightfastness, 40 hours: AATCC 16, Option 1 or 3	8" x 8"	5 - 7 days
<b>Wrapped Panels and Upholstered Walls:</b>		
1. Flammability: ASTM E 84 (Unadhered)	4 yards	4 weeks
2. Crocking (Wet & Dry): AATCC 8	8" x 24"	2 - 3 days
3. Lightfastness, 40 hours: AATCC 16, Option 1 or 3	8" x 8"	5 - 7 days
4. Breaking (Tensile) Strength: ASTM D 5034	12" x 36"	3 - 4 days

NOTES: TO CONDUCT UPHOLSTERY TESTS 1 THROUGH 7 WE REQUIRE 3 YARDS X FULL WIDTH OF FABRIC.

**The tests contained in this list are not to be considered all-inclusive. Other tests not listed might apply. In order to assure that you are considering the proper test, please contact us or complete a "Request for Quote" form.**