



Govmark Flammability Testing



October 2007 (Rev. 5/14/08)

ASTM F 793 – WALLCOVERING

CATEGORY:	TEST METHOD	SAMPLE SIZE:
1. Lightfastness, Carbon Arc, 60, 100 & 200 hours	FTM 5660.1	1 piece: ¼ yard
2. Washability	ASTM F 793 para. 7.4	1 piece: 1 yard
3. Scrubbability	ASTM F 793 para. 7.7	1 piece: 1 yard
4. Abrasion, Wyzenbeek, 220 grit, 300 cycles	FTM 5304	1 piece: ½ yard
5. Tensile (Break) Strength	FTM 5100	1 piece: ½ yard
6. Crocking	FTM 5651, Method B	1 piece: ¼ yard
7. Stain Resistance	ASTM F 793 para. 7.5	1 piece: 1 yard
8. Elmendorf Tear	ASTM D 751 27, Procedure A	1 piece: ½ yard
9. Blocking Resistance	FTM 5872	1 piece: ¼ yard
10. Adhesion of Coating	ASTM D 751 45-48	1 piece: ½ yard
11. Cold Crack Resistance	ASTM F 793 para. 7.13	1 piece: ¼ yard
12. Heat Aging Resistance	FTM 5850	1 piece: ½ yard
13. Flame Spread & Smoke *	ASTM E 84	1 piece: 4 yards
14. Shrinkage	ASTM D 3597	1 piece: ½ yard

Performance Time: 4 weeks for all tests.

Total Yardage Required for Tests 1 through 14: 10 yards

* Same as UL 723.

Testing Services:	See our website to view a listing of the many flammability and physical tests performed by Govmark.
Flammability Testers:	Govmark is also a major supplier of flammability testers. These are also shown on our website.
Publication:	"The Govmark Book on Flammability Standards and Flammability Test Methods." This Govmark publication will offer hundreds of summaries and sketches of the various flammability tests that exist for a multitude of products, both nationally and internationally. Anticipated date of publication: June 2009.