

Specific Test List: Upholstery Cover Materials — Flammability Test Procedures by Ignition Source

Test	Sample Size	Performance Time
CIGARETTE IGNITION RESISTANCE:		
ASTM E 1353 Cover Fabric Test	36" x 48"	5 days
NFPA 260 Cover Fabric	36" x 48"	5 days
UFAC Fabric Classification Test Method	36" x 48"	5 days
CFR 1634 Upholstery Cover Fabric:	5 yards	5 days
BS 5852 Smouldering Cigarette Test	2 yards	5 days
IMO A652 (16) Smoulering Cigarette Test	2 yards	5 days

SMALL OPEN FLAME TESTS:		
CA TB 117 Section E	24" x 24"	5 days
NFPA 701 Test Method #1	1 yard	5 days
FAR Part 25 Appendix F Part I (b) (4) 12-seconds Vertical Test	18" x 36"	5 days
BS 5852 Butane Flame Test	2 yards	5 days
IMO A652 (16) Butane Flame Test	2 yards	5 days
BS 5852 Crib 5	2 yards	5 days

FULL SCALE OPEN FLAME TESTS:		
CA TB 133 Screening Test	3 yards	7 to 10 days
NFPA 266 Screening Test	3 yards	7 to 10 days
ASTM E 1537 Screening Test	3 yards	7 to 10 days

The tests contained in this list are not to be considered all-inclusive. Other tests not listed might apply. In order to assure that you are considering the proper test, please contact us or complete a "Request for Quote" form."

The Govmark Organization, Inc.

96 Allen Boulevard, Suite D • Farmingdale, New York 11735-5626 • United States of America
 Tel: +1 631 293-8944 • Fax: + 1 631 293-8956 • Web: www.govmark.com • Email: info@govmark.com