

Specific Test List: Upholstery Cover Materials - Flammability Test Procedures by Use Category

Test	Sample Size	Performance Time
RESIDENTIAL (PRIVATE RESIDENCES)		
CA TB 117 Section E	24" x 24"	5 days
UFAC Fabric Classification	36" x 48"	5 days

PUBLIC BUILDINGS		
CA TB 117 Section E	24" x 24"	5 days
NFPA 260 Cover Fabric	36" x 48"	5 days
NFPA 701 Test Method #1	1 yard	5 days
CA TB 133 Cover Fabric Prototype	3 yards	7 to 10 days

AIRCRAFT		
FAA 12-seconds Vertical	18" x 36"	5 days
Boeing & Airbus		
12-seconds Vertical	18" x 36"	5 days
Smoke Density Flaming & Non Flaming	18" x 18"	7 to 10 days
Combustion Toxicity	24" x 24"	7 to 10 days

BUSES & RAIL CARS		
12-seconds Vertical	18" x 36"	5 days
Smoke Density	18" x 18"	7 to 10 days

PASSENGER VEHICLES		
USA: CFR Title 49 Part 571.302 (FMVSS 302)	18" x full width	5 days
CANADA: CMVSS 302	18" x full width	5 days
INTERNATIONAL: ISO 3795	18" x full width	5 days

PASSENGER VESSELS		
Cigarette Ignition IMO A652 (16)	2 yards	5 days
Butane Flame Ignition IMO A652 (16)	2 yards	5 days

EUROPEAN PUBLIC BUILDINGS		
BS 5852		
Cigarette Ignition	2 yards	5 days
Butane Flame Ignition	2 yards	5 days
Crib 5	2 yards	5 days

The tests contained in this list are not to be considered all-inclusive. Other tests not listed might apply. In order to assure that you are considering the proper test, please contact us or complete a "Request for Quote" form.

The Govmark Organization, Inc.

96 Allen Boulevard, Suite D • Farmingdale, New York 11735-5626 • United States of America
 Tel: +1 631 293-8944 • Fax: + 1 631 293-8956 • www.govmark.com • Email: info@govmark.com

© The Govmark Organization, Inc. - All Rights Reserved.