

Specific Test List: Wallcovering Flammability: By Occupancy

Test	Product Required	Performance Time
RESIDENTIAL (PRIVATE RESIDENCES)		
ASTM E 84 **	23" +/- 1" x 24 ft.	3 to 4 weeks

PUBLIC BUILDINGS		
ASTM E 84	23" +/- 1" x 24 ft.	3 to 4 weeks
NFPA 265 (TEXTILES)	Sufficient material to cover 2 sections 2' x 8' and 8 sections 4' x 8'	3 to 4 weeks
NFPA 286 (NON-TEXTILES)	Sufficient material to cover 2 sections 2' x 8' and 8 sections 4' x 8'	3 to 4 weeks

PASSENGER VESSELS		
Bulkhead Coverings		
IMO A.653 (16) Surface Flamability	6 pieces: 6.0" x 31.5"	10 to 14 days
IMO A.653 (16) Surface Flamability		
Smoke	1 piece: 18" x 18"	10 to 14 days
Toxicity	1 piece: 30" x 30"	10 to 14 days

AIRCRAFT WALL PANELS		
FAA:		
60-Seconds Vertical	5 pieces: 3" x 12" MD 5 pieces: 3" x 12" CMD	5 days
Rate of Heat Release 65/65	1 piece: 24" x 24"	5 to 7 days
Smoke Density	1 piece: 12" x 12"	5 to 7 days

AIRBUS & BOEING		
60-Seconds Vertical	5 pieces: 3" x 12" MD 5 pieces: 3" x 12" CMD	5 days
Rate of Heat Release 65/65	1 piece: 24" x 24"	7 to 10 days
Smoke Density	1 piece: 18" x 18"	7 to 10 days
Combustion Toxicity	1 piece: 24" x 24"	7 to 10 days

The Govmark Organization, Inc.

96 Allen Boulevard, Suite D • Farmingdale, New York 11735-5626 • United States of America
Tel: +1 631 293-8944 • Fax: + 1 631 293-8956 • www.govmark.com • Email: info@govmark.com

© The Govmark Organization, Inc. - All Rights Reserved.