

Interior Finish

***Please complete a separate form for each product submitted***

**TEST REQUESTED:**     ASTM E84\*;  NFPA 265;  NFPA 286

\* See Page 2 for additional information required for ASTM E84

**PRODUCT DESCRIPTION\*\*:**

**Textile Type Product Identification:** \_\_\_\_\_

**Vinyl Type Product Identification:** \_\_\_\_\_

**Other Identification:** \_\_\_\_\_

Installation Site (*city and state, if known*): \_\_\_\_\_

**\*\* The client should give as much identifying information as possible. Suggested parameters (includes but are not limited to): physical composition, weight, thickness, color, etc.**

**PLEASE INDICATE END USE CONFIGURATION (For NFPA 265 and NFPA 286. See Page 2 for ASTM E84)\*\*\*:**

- The product will be bonded to a gypsum (sheetrock) wall
- The product will be used on a non-combustible surface
- The product will be used as a panel covering fabric
- The product is self-supporting
- The product is a site-fabricated stretch system
- Other (please describe): \_\_\_\_\_

**\*\*\*This information is necessary, as it helps to determine the configuration and mounting means of the test. Certain codes require certain test configurations.**

-- Continued on Page 2 --

Interior Finish

### Additional Information Required for ASTM E84

- Self-supporting (non-substrate)**
- Unadhered (chicken wire/rods, non rigid material)**
- Adhered by client (no labor to be provided)**
- Adhered by lab:**

Substrate to Be Used<sup>1</sup>:     Standard 5/8" thick Type X Gypsum  
 1/4" Inorganic Reinforced Cement Board (IRC)  
 Other (*please specify*): \_\_\_\_\_

Adhesive to Be Used<sup>2</sup>:     None  
 Adhesive:                     Supplied by client  
                                                  Supplied by lab (*additional charges apply*):  
                                                 Brand: \_\_\_\_\_  
                                                 Type: \_\_\_\_\_

Trowel to Be Used<sup>2</sup>:     Supplied by client  
 Supplied by lab:    Size:     1/8"             1/16"  
                                                 Type:     Open             Flat             Notched

<sup>1</sup> If this item is not selected by client, SGS Govmark will use the standard 5/8" Type X Gypsum board.  
<sup>2</sup> If this item is not selected by client, SGS Govmark will select and use an appropriate adhesive and trowel to affect a satisfactory adhesion of the submitted material to the substrate.

**ASTM E84 Plastics/Polymers Policy**

Please note that all plastics and/or polymeric materials are charged at a higher test fee because of the required cleanup of the tunnel after testing.

SGS Govmark limits flame spread and smoke developed evaluation of plastics and other polymer based compounds of **unknown** combustibility and smoke generating characteristics to a maximum thickness of 0.125" and submitted in flat sections only sufficient to achieve the required specimen length.

Specimens of greater thickness may be conducted if, after screening by lab personnel, a judgment is rendered to proceed to test.

The test will be terminated **at any time** when:

1. The smoke developed exceeds 500 rendering the material unclassifiable;
2. The temperature at the 24-ft. end of the tunnel exceeds 1,250°F; OR
3. When, in the judgment of the test operator, the safety of personnel or the threat of the equipment and/or environment is deemed to be probable.

-- Continued on Page 3 --

Interior Finish

**SPECIAL INSTRUCTIONS:** All special instructions contained in your purchase order, such as testing modifications, extra report copies, invoice distribution, etc., must be repeated on this test order form.

Testing will be conducted as directed by this test order form which supersedes the purchase order.

---



---



---



---

**COMPANY DATA:** Please complete all three columns. Where appropriate, "same" may be entered in Columns 2 and 3.

Unless otherwise instructed, all reports will be sent to the company identified in Column 1.

	(1)	(2)	(3)
	COMPANY SUBMITTING SAMPLE	COMPANY TO APPEAR ON REPORT	COMPANY BILLING ADDRESS
Person's Name:			
Company Name:			
Address:			
Telephone #:			
E-mail:			

**CLIENT UPDATE (OPTIONAL):**

Existing account;  New account

*In a few words, what brought you to SGS Govmark?* \_\_\_\_\_

\_\_\_\_\_

-- Continued on Page 4 --

Interior Finish

DO YOU REQUIRE YOUR SAMPLES TO BE RETURNED TO YOU:  NO;  YES      CARRIER: \_\_\_\_\_  
ACCOUNT #: \_\_\_\_\_

**LITIGATION:** *We need to know if the test is part of a lawsuit.*

**IS THIS TESTING PART OF ANY ACTUAL OR INTENDED LEGAL ACTION, CLAIM, OR SIMILAR ACTION?**  NO\*;  YES  
\* Failure to answer will be considered “no”.

**SEND SAMPLES TO:**

**SGS GOVMARK  
96 ALLEN BOULEVARD, SUITE D  
FARMINGDALE, NY 11735 U.S.A.**

Federal EIN # 27 4458985

Tel. +1 631-293-8944  
Fax +1 631-293-8956  
E-mail: [rosemary.billelo@sgs.com](mailto:rosemary.billelo@sgs.com)

SAMPLES THAT ARE RECEIVED WITHOUT APPROPRIATE INFORMATION MAY BE DELAYED IN TESTING PENDING RECEIPT OF SUCH INFORMATION.

NAME OF PERSON COMPLETING FORM: \_\_\_\_\_      DATE: \_\_\_\_\_